

stop crime fast with the

SENTINEL S35

EFFECTIVE | VERSATILE | ECONOMICAL | COMPACT



sen-ti-nel n. A guard whose job it is the stand and keep watch

Suitable for a wide range of applications

Quality assured performance and reliability

Simple installation and integration

The Smoke Screen Sentinel range has been designed and manufactured for permanent installation either as a fully integrated part of an intruder alarm system or as a stand-alone system. The range comprises some of the most advanced security smoke generators in the world.

The new, precision cast aluminium heater block offers high performance levels and reliability. This translates to a more impressive volume of drier fog (no residue) that lasts for even longer.

The Sentinel S35 is the smallest Smoke Screen in the Sentinel range. Its compact size and impressive performance make the S35 suitable for almost any application, where fast acting thieves may strike.

New PCB technology, ergonomic connectors and multi-bracket design make installation easy and straightforward. Other features such as the internal battery back-up and a multi-nozzle system make the S35 incredibly versatile.



'ANTI-RAID' FIRST BURST

Turbo mode for maximum smoke generation in risk critical areas designed to stop thieves in their tracks.

VERSATILITY IS KEY

Compact and inexpensive, suitable for private homes, server rooms, small offices, stores, window displays and more.

MULTI-NOZZLE OPTIONS

A range of different nozzles are available to produce a range of different effects. This makes installation even easier.

FEATURES

- 3-year warranty.
- 55 second initial burst for maximum smoke generation in risk critical areas.
- Off-mains operational capability.
- Energy save mode cuts costs in periods when the generator is not immediately needed.
- Supports automatic re-firing via screen-sensor technology.
- Extreme temperature operation: -10°C to 50°C.
- £10 million product and public liability insurance.

OPERATION

- 4 inputs and 7 outputs.
- LCD status display and on-board event log.

CONSTRUCTION

- Rugged and compact steel casing in pure white.
- Environmental pack for installation in confined spaces with elevated ambient temperatures.
- Aluminium heater block allows use of most persistent smoke chemical.

STANDARDS COMPLIANCE

- EN50131:8 and IEC62642:8.
- CNPP Rating: Class I Category 30.

FLUID

- 500ml/5,000ml fluid system.

DATA

- 37.9(H)* x 14(D) x 23.2(W) cm *add 0.5cm for feet.
- Weight: 9.6kg (pre-install), 11kg (installed).

CAN'T SEE IT? CAN'T STEAL IT!